

Vaisala HUMICAP® Humidity and Temperature Transmitter HMS110

Vaisala HUMICAP® Humidity and Temperature transmitter				HMS110	2			V	A		N	N	PRICE
1	Output signals	4 ...20 mA			2								
2	Measured parameter for channel 1	RH				A							
		Td	(-40 ... +60°C)			B							
		T	(-40 ... +60°C)			C							
		Tw	(-40 ... +60°C)			D							
		h	(-40 ... 460 kJ/kg)			H							
		<i>Td, free scale scale</i>	<i>Low High °C</i>			<i>X</i>							
		<i>Tw, free scale scale</i>	<i>Low High °C</i>			<i>Y</i>							
		<i>h, free scale scale</i>	<i>Low High kJ/kg</i>			<i>Z</i>							
3	Measured parameter for channel 2	Td	(-40 ... +60°C)			0							
		T	(-40 ... +60°C)			1							
		T	(-5 ... +55°C)			2							
		T	(0 ... +50°C)			3							
		<i>T, free scale</i>	<i>Low High °C</i>			<i>X</i>							
5	Humidity sensor	Humicap180R						A					
6	User guide	No user guide								0			
		Multilingual quick guide								1			
										TOTAL			
										QTY			
										TOTAL VALUE			

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMS110	2	A	1	V	A	1	N	N
--------	---	---	---	---	---	---	---	---

